

AUTOTRONIC 25 BOOST 230V 12-24V code 807540

Battery charger with electronic control of the charging current, automatic interruption and restart (TRONIC), for charging lead-acid batteries with 12/24V voltage. Fit with switches to choose either normal charge (MIN) or quick charge (BOOST) in the buffer mode (TRONIC) or drooping characteristic mode (CHARGE). The buffer automatic charge is adequate for maintenance free sealed batteries (GEL/AGM), while the drooping characteristic charge is adequate for free-electrolyte batteries (WET). Characteristics: choice of output voltage, type of charge, charging mode * display of charging current * protection against overloads and polarity reversal.



Tronic



Pb-Ca

Gel/Agm

AUTOMOTIVE

PROFESSIONAL



Technical Data

Standards:	LVD: EN 60335-2-29	EMC: EN 55014-1,2;	EMC: EN 61000-3-2,3				
CODE	V _{PH}	P	+ - START	A _{EFF}	A _{EN}	C MIN/MAX	C MIN/MAX
807540	V50/60Hz 230 1 ph	W 300	V 12 24	A 18 12	A 12 8	Ah 30 225	Ah 20 180
	W _H	kg	BAR CODE				
4	mm(L,W,H) 225 290 205	kg 7,2	800489764142 3	pz/pallet 56	pz/pallet - B 42		