


# Sonnenschein – A508/3.5 S data sheet

## Terminal



## Specifications:

Part numbers not valid for North America, use type for ordering!

GNB type designation	Nom. Voltage V	Nom. capacity C <sub>20</sub> 1.75Vpc 20°C Ah	Length (l) max. mm	Width (b/w) max. mm	Height top of cover (h1) max. mm	Height over terminals (h2) max. mm	Weight approx. kg	Internal resistance mOhm	Short circuit current A	Max. Load approx. A	Max. perm current 5 secs. A	Terminal
A508/3.5 S	8	3.50	179	34.1	60.5	64.4	1.00	95	88	60	300	S-4.8

## Constant-current discharge in A @ 20 °C

Part number	Vpc	5 min	10 min	15 min	20 min	30 min	1 h	2 h	3 h	5 h	8 h	10 h
NGA50803D5HS0SA	1.85	9.50	6.70	5.50	4.50	3.40	2.10	1.40	0.95	0.60	0.39	0.32
NGA50803D5HS0SA	1.80	10.6	7.40	6.00	4.90	3.70	2.20	1.40	0.98	0.62	0.40	0.33
NGA50803D5HS0SA	1.75	11.3	7.90	6.20	5.10	3.80	2.30	1.40	0.99	0.62	0.41	0.34
NGA50803D5HS0SA	1.70	12.1	8.30	6.30	5.20	3.90	2.30	1.40	1.00	0.63	0.41	0.34
NGA50803D5HS0SA	1.65	12.7	8.50	6.50	5.30	3.90	2.30	1.40	1.01	0.63	0.41	0.34
NGA50803D5HS0SA	1.60	13.1	8.70	6.50	5.30	3.90	2.30	1.40	1.01	0.63	0.41	0.34

## Constant-power discharge in W/block @ 20 °C

Part number	Vpc	3 min	5 min	10 min	15 min	20 min	30 min	45 min	1 h	1.5 h
NGA50803D5HS0SA	1.85	83.0	68.0	51.0	42.0	35.0	27.0	22.0	17.0	12.0
NGA50803D5HS0SA	1.80	91.0	76.0	56.0	44.0	37.0	28.0	23.0	18.0	13.0
NGA50803D5HS0SA	1.75	97.0	82.0	60.0	46.0	39.0	29.0	23.0	18.0	13.0
NGA50803D5HS0SA	1.70	106	88.0	61.0	48.0	40.0	30.0	24.0	19.0	13.0
NGA50803D5HS0SA	1.65	113	91.0	62.0	49.0	41.0	30.0	24.0	19.0	13.0
NGA50803D5HS0SA	1.60	119	93.0	63.0	49.0	41.0	30.0	24.0	19.0	13.0

## Sonnenschein A508/3.5 S drawing

