



JHCD CD-4212-1 Battery Charger

Lifeboat battery charger, it is specially used for the automatic compensating charge the battery which are used on the lifeboat or ship.

- **Brand:** JHCD, JIANGHAI SHIPPING ELECTRIC
- **Yellow Lamp:** Charging, CD4212-1 will charge automatically if the voltage of the battery is lower than 13.3V.
- **Green Lamp:** Fully Charged, CD4212-1 will stop charge automatically if the voltage of the battery is charged to 14.4V.
- **Red Lamp:** Failure, CD4212-1 red lamp will flash there is open circuit, reverse polarity, short circuit.
- **Main Voltage:** 42V AC
- **Charge Voltage:** 1x12V DC
- **Charge Current:** 1x5A DC
- **Protection:** IP56
- **Trouble Shooting:** CD-4212-1 yellow lamp flashing, the battery is aging, change the battery.
- **Trouble Shooting:** CD-4212-1 red lamp flashing, the output cable is connected reversibly to the battery.
- **Warning:** CD4212-1 lifeboat battery charger can only be used to make compensating charge for the battery.
- **Important Information:** Always disconnect input VAC (mains) before connecting or disconnecting batteries.
- **Working Temperature:** -25°C ~ 55°C
- **HS Code:** 8504409999
- **Dimension:** 160 x 120 x 85 mm
- **Weight:** 3Kg
- **Class Certificate:** ABS , BV , CCS , DNV , GL , LR , KR , NK , RINA , RS