

STS600 BATTERY TESTER



- Digital tester with graphic display.
- For 8-240Ah batteries at 12/24V.
- Tests carried out: battery status, cranking efficiency, of the cranking system and the alternator circuit.
- Includes software to print reports via connection to the PC.

DESCRIPTION

Digital tester to check the status of the battery, the starting efficiency (CCA), the starter system and the alternator circuit of the vehicle.

Selectable international standards for cars, which correspond to different starting current ranges used by the battery manufacturer.

Handy and small in size, it can operate on 12V batteries (WET, GEL, MF, AGM, PbCa, EFB) both disconnected and connected to the vehicle, making testing operations quick and easy.






The graphic display makes the product intuitive and easy to use.

Printing of reports via PC connection.

Features:

- for WET, GEL, MF, AGM, PbCa, EFB batteries from 8-240 Ah at 12V;
- tests performed: battery status, starting capability (CCA), starter system, vehicle alternator circuit;
- selectable reference standards for cars;
- tests can be performed with the battery disconnected or connected to the vehicle;
- graphic display;
- multilingual: EN, IT, FR, DE, ES, RU, PT, NL;
- printing of reports via PC connection.

TECHNICAL DATA

CODE	CODE 804242		Battery voltage 12 V	A_h	Battery range 8-240 Ah
A_{MIN} MAX	Starting current range EN 100/2000-EN A		Starting current range IEC 100/1400-IEC A	A_{MIN} MAX	Starting current range DIN 100/1400-DIN A
A_{MIN} MAX	Starting current range SAE 100/2000-SAE A		Starting cur.range CA(MCA) 100/2000-CA(MCA)-CCA-BCI A	A_{MIN} MAX	Starting current range JIS 26A17/245H2-JIS A
T^{°C}	Operating temper.(min-max) 0 - 40 °C		DIMENSIONS 8,0 x 2,4 x 15,0 cm		WEIGHT 0,26 kg

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SOFTWARE/APP