

# STS700 BATTERY TESTER



- Digital tester with colour, graphic display.
- For 8-240Ah batteries at 12/24V.
- Tests carried out: battery status, cranking efficiency, of the cranking system and the alternator circuit.
- Includes software to print reports via connection to the PC.

## DESCRIPTION

Digital tester to check the status of the battery, the starting efficiency (CCA), the starter system and the alternator circuit of the vehicle.

Selectable international standards both for cars and motorbikes, which correspond to different starting current ranges used by the battery manufacturer.

Handy and small in size, it can operate on 12V batteries (WET, GEL, MF, AGM, PbCa, EFB) both disconnected and connected to the vehicle, making testing operations quick and easy.

The colour graphic display makes the product intuitive and easy to use.










It is possible to graphically display the performance of the battery voltage over time.

Saving and printing of reports via PC connection.

Features:

- for WET, GEL, MF, AGM, PbCa, EFB batteries from 8-240 Ah at 12V;
- tests performed: battery status, starting capability (CCA), starter system, vehicle alternator circuit;
- selectable reference standards for cars and motorbikes;
- tests can be performed with the battery disconnected or connected to the vehicle;
- color graphic display;
- graphic display of voltage performance over time;
- multilingual: EN, IT, FR, DE, ES, RU, PT, NL, PL, JP, CN, KO;
- saving and printing of reports via PC connection.

## TECHNICAL DATA

 <b>CODE</b>	CODE 804243	 <b>Battery voltage</b>	12 V	 <b>Battery range</b>	8-240 Ah
 <b>A MIN MAX</b>	Starting current range EN 185/1125-EN A	 <b>A MIN MAX</b>	Starting current range IEC 100/1400-IEC-DIN A	 <b>A MIN MAX</b>	Starting current range DIN 26A17/245H2-JIS A
 <b>A MIN MAX</b>	Starting current range SAE 200/2000-SAE A	 <b>A MIN MAX</b>	Starting cur.range CA(MCA) 100/2000-CA(MCA)-CCA-BCI A	 <b>A MIN MAX</b>	Starting current range JIS 12N5.5-4A,12N5.5A-3B (MOT) A



Operating temper.(min-max)  
0 - 40 °C



DIMENSIONS  
8,0 x 2,3 x 15,0 cm



WEIGHT  
0,27 kg

## DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL



SOFTWARE/APP