

TOURING 15



ELEMENTS *Tronic*

12V

24V

Pb-Ca

Wet

Gel

AGM

EFB

MF

- Battery charger with TRONIC technology for WET, GEL, Pb-Ca, AGM, MF, EFB 12/24 V batteries.
- Battery charge status LED signal. Key to set the voltage (12 and 24 V).
- Protection against overcharging, pole inversion and recognition of charge voltage.
- Light and compact: only 2.9 kg.

DESCRIPTION

Battery charger with electronic control of the charging steps, automatic interruption and restart (TRONIC), for charging WET, GEL, Pb-Ca, AGM, MF, EFB batteries with 12V/24V voltage.

With warning LED to indicate battery charge status.

Fit with protection against overloads and polarity reversal and recognition of battery voltage.



TECHNICAL DATA

CODE	CODE 807592	V_{1PH}	SINGLEPHASE MAINS VOLTAGE 230 V	F	MAINS FREQUENCY 50 / 60 Hz
P	CHARGING ABSORBED POWER 130 W		CHARGING VOLTAGE 12 / 24 V	A_{EFF}	EFFECTIVE CHARGING CURRENT 12 / 6,5 A
A_{EN}	RATED CHAR.CUR.EN60335-2-29 6 / 4,5 A		MIN.RATED REFERENCE CAPAC. 50 / 30 Ah		MAX.RATED REFERENCE CAPAC. 115 / 55 Ah
	DIMENSIONS (LxWxH) 10 x 19 x 19 cm		WEIGHT 2,93 kg		

ON REQUEST ACCESSORIES



FUSES 10A 10 PCS
802255

DOWNLOAD



CATALOG IMAGE



INSTRUCTION MANUAL

USEFUL LINKS



VIDEO