





Drawings & Terminal Position



ODP-AGM49/H8/L5 RIGHT POSITIVE SAE TERMINALS



Handling and Storage

- Can be mounted or stored in any orientation except
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

PDF Generated at https://eu.odysseybattery.com 01/10/2024 06:53:16

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODP-AGM49 H8 L5

(49-950 (LN5-H8))

Battery Type

- With SAE posts
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	1700A
Cold Cranking Amps (CCA)	950A
HCA	1300A
MCA	1150A
20Hr Nominal Capacity (Ah)	95Ah
10Hr Nominal Capacity (Ah)	85Ah
Reserve Capacity Minutes	190 mins
Terminal	SAE
Torque Spec in-lbs (Nm max)	N/A
Internal Resistance (m Ω)	$4.8~\text{m}\Omega$
Short Circuit (A)	2650A
UPC	635241140774

Dimensions and Weight

Length	13.9 in / 353 mm
Width	6.9 in / 175 mm
Height (terminals included)	7.4 in / 188 mm
Height (container)	7.5 in / 191 mm
Weight	62.8 lbs / 28.5 kg

Temperature

Operating temperature range -40°F / -40°C to 140°F / +60°C Optimum storage temperature 68°F / +20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters

2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837

EnerSys EMEA

EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland **EnerSys Asia** 152 Beach Road #11-08 Gateway East

Building Singapore 189721 Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library

