




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve	IUU
Charger voltage at 68°F (20°C)	14.4V to 14.8V
Self-discharge per month at 68°F (20°C)	1.25%
Self-discharge per month at 104°F (40°C)	5%
80% depth of discharge cycles	400

EnerSys World

Headquarters

2366 Bernville Road

Reading, PA 19605, USA 6300 Zug, Switzerland Tel: +1-800-964-2837 Singapore 189721

EnerSys Asia 152 Beach Road #11-08 Gateway East

Building Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library

Technical Data Sheet

ODX-AGM34 78

(34/78-PC1500)

website for updates.

Battery Type

- Group 34/78 with tin-plated brass SAE automotive top posts & 3/8 inch threaded side receptacles
- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)

PDF Generated at https://eu.odysseybattery.com 01/09/2024

Information correct at time of exporting PDF. Please check

• Advanced dual purpose battery for engine start and deep

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	1500A
Cold Cranking Amps (CCA)	850A
HCA	1250A
MCA	1050A
20Hr Nominal Capacity (Ah)	68Ah
10Hr Nominal Capacity (Ah)	62Ah
Reserve Capacity Minutes	135 mins
Terminal	SAE & Side
Torque Spec in-lbs (Nm max)	60 (6.8) side terminal only
Internal Resistance (m Ω)	$2.5~\text{m}\Omega$
Short Circuit (A)	3100A
UPC	635241140422

Dimensions and Weight

Length	10.9 in / 277 mm
Width	6.8 in / 173 mm
Height (terminals included)	7.9 in / 201 mm
Height (container)	7.3 in / 185 mm
Weight	49.5 lbs / 22.4 kg

Temperature

Operating temperature range -40°F/-40°C to 176°F/+80°C Optimum storage temperature 68°F/+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016

EnerSys EMEA

EH Europe GmbH

Baarerstrasse 18