




Drawings & Terminal Position



Handling and Storage

- Can be mounted or stored in any orientation except
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

Type of charging curve IUU Charger voltage at 68°F (20°C) 14.4V to 14.8V Self-discharge per month at 68°F (20°C) 1.25% Self-discharge per month at 104°F (40°C) 5% 80% depth of discharge cycles 400

PDF Generated at https://eu.odysseybattery.com 01/10/2024

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet ODS-AGM30L

Battery Type

- Absorbed Glass Mat (AGM) with Thin Plate Pure Lead (TPPL)
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

Voltage	12V
Pulse (5 second) Hot Cranking Amps (PHCA)	720A
Cold Cranking Amps (CCA)	400A
HCA	575A
MCA	500A
20Hr Nominal Capacity (Ah)	30Ah
10Hr Nominal Capacity (Ah)	27Ah
Reserve Capacity Minutes	50 mins
Terminal	M6 Receptacle
Torque Spec in-lbs (Nm max)	50 (5.6)
UPC	635241142372

Dimensions and Weight

Length	6.6 in / 168 mm
Width	4.9 in / 124 mm
Height (terminals included)	6.9 in / 175 mm
Height (container)	6.9 in / 175 mm
Weight	20 lbs / 9.1 kg

Temperature

Operating temperature range $-40^{\circ}F/-40^{\circ}C$ to $140^{\circ}F/+60^{\circ}C$ 68°F/+20°C Optimum storage temperature

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters 2366 Bernville Road

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 Reading, PA 19605, USA 6300 Zug, Switzerland Tel: +1-800-964-2837

EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800

Want more info? Scan code to access the ODYSSEY® Battery Literature Library

